Scriptel® ScripTouch® Compact 1X5 USB

Electronic Signature Pad

ST1550 ProScript Device Interface ST1551 EasyScript Device Interface



The ScripTouch Compact 1X5 USB signature pad features an easy to carry and store form factor with backlit LCD for immediate rendering and visual feedback to the signer that is ideal for professionals that need to capture electronic signatures on the go.

Scriptel's Compact signature pad is available in EasyScript and ProScript device interfaces.

The EasyScript device interface is unique to Scriptel and is especially interesting for pure cloud-based applications that need to work across the major browsers and across Windows, Mac and Linux. With appropriate design, no software install is needed on the client PC.

The ProScript device interface supports communication between the signature pad and software applications that have embedded Scriptel APIs or use the Scriptel OmniScript universal signature integration platform.

Available Software and Integration Support for: EasyScript (ST1551) ProScript (ST1550)

- Microsoft Word and Excel plugins
- Adobe Acrobat and Reader plugins
- ScripTouch Sign and Save signature image and data capture application
- Supports OmniScript universal signature integration platform
- Extensive APIs and software libraries in .NET (C++,VB, C# and F#)
- Windows COM
- Software libraries and examples in Java, JavaScript, PHP, ASP .NET, C, C++ and Objective C
- APIs and software libraries also available for .NET (C++, VB, C# and F#)

Ruggedly Reliable Best Service in Industry Software Excellence

Key Features:

- Compact design
- Backlit LCD
- Scratch-resistant glass signing surface
- Active battery-less tethered pen
- Durable plastic case construction with replaceable cables
- Bottom-side rubber feet
- ProScript & EasyScript Device **Interfaces**

3 Year Warranty 30 Day free evaluation RapidCare replacement[†]

www.scriptel.com

2174 Dividend Drive Columbus, Ohio 43228 Telephone - 877.848.6824 Fax - 614.276.7615

Scriptel [®] ScripTouch [®] Compact 1X5 USB

Electronic Signature Pad

ST1550 ProScript Device Interface ST1551 EasyScript Device Interface

Specifications

•		
Active Signature Area	4.25" x 1.2" (107.9 x 30.5 mm)	
Signature Display	Monochrome backlit LCD (240x64 pixels), signature rendered immediately	
Pen Type	Active battery-less tethered pen	
Sensing Technology	Scriptel StaticCap capacitive sensing	
Min Signature Resolution	500 ppi	
Min Signature Sampling Rate	120 pps	
Product Dimensions	5.2" x 0.68" x 3.2" (132.1 x 17.3 x 81.3mm)	
Data Interface	USB 2.0 (standard A-type connector)	
Power Supply	USB bus-powered, no separate external power supply needed	
Operating Systems	Support available for Windows, Mac OS, Linux	
Warranty	3 Year	
	ST1550	ST1551
Data Protocol	Scriptel ProScript device interface	Scriptel EasyScript device interface
Development Environments	.NET, COM, JavaScript, Java, PHP, WebSockets and others on request	C, JavaScript, Java, .NET, PHP and others on re- quest
Downloadable Software	ScripTouch Sign and Save, ScripTouch Toolbox, OmniScript universal sig- nature integration platform, Word, Excel and Adobe plugins	ScripTouch Toolbox

Ruggedly Reliable
Best Service in Industry
Software Excellence

Key Features:

- Compact design
- Backlit LCD
- Scratch-resistant glass signing surface
- Active battery-less tethered pen
- Durable plastic case construction with replaceable cables
- Bottom-side rubber feet
- ProScript & EasyScript Device Interfaces

3 Year Warranty 30 Day free evaluation[†] RapidCare replacement[†]

www.scriptel.com



2174 Dividend Drive Columbus, Ohio 43228 Telephone - 877.848.6824 Fax - 614.276.7615